

EMAIL COMPLETED FORM TO SALES@MOBILITYINNOVATORS.COM MILFORD ASSESSMENT FORM



Customer Details																
Height:		V	/eight:			Age:		Di	isability	:						
					Sling ⁻	Types 8	k Size <mark>(</mark> S	Specialt	y Slings	s cost e	xtra)					
St	tandar	d	D	ouble A	mpute	е	Ne	et/Mes	h		Fleece Lined Head-Supported					
													9			
XS S M L XL S						S M L (Upcharge)			M L (Upcharge)			S M L (Upcharge)				
(Upcharge) (Upcharge) (Upcharge) Sling Size Guide																
HEIGHT height in ft. 3ft 3in 3ft 6in 3ft 9in 4ft 4ft 3in 4ft 6in 4ft 9in 5ft 5ft 3in 5ft 6in 5ft 9in 6ft 6ft 3in 6ft 6in 6ft 9in																
	510	Sit Sill	Sitom	510 511		410 511	410 011	410 5111	511	510 511	Sittom	Sitsii		on sin		one sin
weight in lbs.		X SMALL			SN	IALL		MEDIUN	Л		LAI	RGE		X LARGE		
56 63																
70																
77 84																
91 98																
105																
112 119																
126 133																
133																
147 154																
161																
168 175																
182																
189 196																
203 210																
217																
224 231																
238																
245 252																
259																
266 273																
280 287																
287 294																
301 308																
315																
322		is 330lbs						age 1 -								

MILFORD ASSESSMENT FORM Vehicle Details

	Vehicle Details	
Make:	Model:	Year:
Installation Position:		_
Rear Right Side	Front Right Side	Driver Side = Front Left Side Passenger Side = Front Right Side Rear Passenger Side = Rear Right Side Rear Driver Side = Rear Left Side
Rear Left Side	Front Left Side	
-	The ground to pression in seat. X: From the ground to top of wheelchair seat.	-
	Sill Bracket	
Sill Brackets are used on vehicles dash or to retain the use of the glu typically used in smaller vehicles a be removed before closing the ve	ovebox. This is and will need to	

If Mounting Post will obstruct

the glove box, a Sill Bracket is

recommended.

If there is less than 7" of space

from the door sill to the

bottom of the dash, a Sill Bracket is required.

*Using a Sill Bracket will reduce the weight capacity by 55lbs., minimize foot/leg space & can not be used with vehicle specific applications (unless designed in conjunction)

Does the vehicle need a Sill Bracket?

Yes _____ No _____

- Page 2 – MILFORD ASSESSMENT FORM

Other Options & Accessories

Spreader Bar



A Spreader Bar is included with your Milford Order

Sm (11.25") _____ Med (13.5") _____ Lg (17.5") _____

The Spreader Bar should be at chest height when lifting the client. In some cases, a protective padded cover may be appropriate for the client.

Spreader Bar Covers are additional cost

Spreader Bar Cover: Yes _____ No _____

More ways to use your Milford!



Make your Milford mobile with the Smartbase from Autochair! The Smartbase allows the Milford to be positioned around your home as needed for easy transfers.

- Can lift up to 330lbs
- Wheels lock for safety and stability
- Simple to assemble and operate
- Leg width can be adjusted to suit the space
- Rechargeable battery included
- Portable Folds flat for easy storage

Add	Smartbase t	o quote?	Yes	No

Include Extra Battery (additional cost): Yes____



The Wall Bracket allows your Milford to operate from a fixed position in the home where space is tight. After securely mounting the Wall Bracket to a load-bearing wall, the Milford can help with transfers from wheelchairs to bathtubs, stairlifts to wheelchairs, and anything in between.

Wall Brackets must be mounted on a load-bearing stud wall and may require reinforcement in certain situations.

Rechargeable battery pack not included (must be ordered separately).

If you would like to include Wall Brackets with your order, please let us know by requesting a Wall Bracket Assessment Form.

No